

300 Series

Product Information

Monomeric PVC (gloss/matt, 70 μ) with clear, ecological compatible dispersion adhesive (semi-permanent), laminated on an one-sided clay-coated silicone paper liner (120 g/m²).

A perfect glossy/matt face film in addition to high flexibility and comformability makes the product suitable also for non-smooth surfaces. Especially designed for vehicle lettering, decorating of windows, signs, etc. with excellent plotting, weeding and application characteristics.

Suitable for in- and outdoor mid-term applications.

Particularly suitable for application on flat and slightly curved surfaces. No adhesive residue after removal, if correctly applied.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Available Colours

39 gloss 35 matt

Technical Data

Carrier: monomeric PVC, highly stabilized,

calendered

Thickness: 70 μ +/- 5 %

Adhesive: clear acrylic dispersion,

semi-permanent

Adhesion: 4 N/cm +/- 5%

Liner: one-sided clay-coated

silicone paper (120 g/m^2)

Tensile strength md: >8,8 kN/m

Tensile strength cd: >5,0 kN/m

Application temperature: +10 - +40 °C

Service temperature: - 20 - +50 °C

Outdoor durability: 3-5 years

Standard Dimensions:

1220 mm x 50 m

original material.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the

Siège social : 111, Rue Mustapha Mohsen, 2073 Borj Louzir, Ariana - Tél. : 70 69 48 88 - Fax : 70 69 48 55 Point de vente Sousse : Route ceinture Hammam sousse, 4011 Hammam sousse - Tél : 73 32 44 22 - Fax : 70 69 48 55

www.sotuma.tn

30/08/2011